

Action Herculan ReTop

RT is specifically engineered as a premium re-topping polyurethane for old urethane or rubber floors. Designed to deliver a strong overlay for existing cracked, damaged, or worn-out sports floors.



Repairs should be made to the existing surface—filling-in all cracks, missing flooring, and loose areas. Thoroughly clean the existing surface to remove all contaminants and waxes. Lightly sand/screen the cleaned existing surface to ensure proper bonding. Pour the new RT 210 resin, color coat, and game line, the previous exhausted surface looks and plays like new.

Action Floor Systems, LLC

4781 N US Hwy 51
Mercer, WI 54547
www.actionfloors.com

Phone: 800-746-3512
Fax: 715-476-3585
Email: info@actionfloors.com



Action Herculac RT Floor System

RT 210

Surface Hardness (DIN 53505, ASTM D-2240)	Shore A=76
Impact Resistance (EN 1517-1999, DIN 18032)	12Nm
Resistance - Static Load (24 Hrs)	25 Kg/cm sq
Tensile Strength (EN ISO 527-1, DIN 53455)	12 N/mm sq
Elongation at Break (EN ISO 527-1, DIN 54455)	220%
Tear Strength (DIN 53515)	30 N/mm
Friction (DIN 18032)	0.46



RT System provides a strong and durable surface renovation

Non-porous and hygienic

Quick and reasonable surface renovation

RT210 resin is specifically engineered for resurfacing polyurethane floors