

ACTION REFLEX

SPORTS FLOORING

A extremely durable surface that offers protection for high use areas like free weight rooms, cardio machine settings and strength conditioning areas



Action's ReFlex flooring offers design flexibility with multiple thickness options and a wide range of color fleck options and densities. Reflex is available in rolls, square edge or interlocking tiles.



ACTION REFLEX

SPORTS FLOORING SOLUTIONS



Prominent Features

- Made from recycled material
- Non-slip surface
- Noise attenuation
- Easy maintenance

Test Results

Durometer, Shore A	ASTM D2240-97	60
Density, Lbs/sq ft	ASTM D297-93 P-A,16.3	64
Coefficient of Friction	ASTM D1894-95	
	Dry	1.33
	Wet	1.56
Flammability & Flame Spread	DOC FFI-70 CSP	Pass

Product Specifications

Reflex Floor system recycled rubber with EPDM color fleck granules

EPDM color fleck available from 0% to 90%

Roll Size: 48" wide x minimum of 30' (standard length)

Tile Size: 36" x 36" (less interlocking tabs)

Standard Color: Black

Standard EPDM: 10% color fleck mix

Standard Colors: red, blue, green, gray, tan, eggshell, yellow, purple, orange or teal color fleck



ACTION FLOOR SYSTEMS LLC
4781 N. U.S. Hwy. 51
Mercer, WI 54547-9708 U.S.A.

PHONE: 800.746.3512 or 715.476.3512

FAX: 715.476.3585

E-MAIL: info@actionfloors.com

www.actionfloors.com

