



Action QuickCourt MT

Modular Athletic Flooring

SPORTS FLOOR SPECIFICATIONS

SYSTEM SUMMARY

Action's QuickCourt MT outdoor modular flooring is an economical, durable, easy-to-maintain interlocking tile surface. QuickCourt MT flooring is made with an open grid design from high-impact polypropylene that has a full-suspension system for maximum vertical shock resistance.

Contact ACTION FLOORING SYSTEMS at www.actionfloors.com or (800)746-3512 for specific project conditions or modifications of this specification.

PART 1 – GENERAL

1.01 DESCRIPTION

A. Scope:

1. Complete installation of the interlocking flooring system including the game lines and transitions.

B. Related Sections: Cast-in-Place Concrete

1. A level slab, steel troweled to a tolerance of 1/8" (3mm) in a 10'0" (3m) radius and subject to the approval of the floor contractor.
2. Action Flooring Systems, LLC does not acknowledge the use of FF/FL numbers to measure levelness/flatness tolerances in concrete slabs.
3. Leveling compound to correct minor subfloor cracks, grooves, voids, depressions, or other deviations.

1.02 QUALITY ASSURANCE

- A. All system component parts must be supplied by Action Floor Systems, LLC.
- B. Manufacturer shall be an established firm specializing in the manufacturing of the products specified in this section and have been in business a minimum of ten (10) years.
- C. Manufacturer shall be ISO 9001:2008 Certified to assure proper quality control.
- D. Flooring system shall be independently tested and meets or exceeds athletic performance requirements as specified. Independent testing laboratory shall have Scientific Body Membership in the International Association of Sports Surface Sciences (ISSS).
- E. The complete installation of the flooring system as described in these specifications shall be carried out by an experienced installer (Flooring Contractor) as approved by Action Floor Systems, LLC.. The work shall be performed in accordance with current installation instructions. The installer shall be liable for all matters related to the installation of the products described herein for a period of not less than one (1) year from the date of installation completion.

1.03 SUBMITTALS

- A. Manufacturers product data: Submit **Action's QuickCourt MT** specification sheets.
- B. Samples: Submit one (1) sample of **QuickCourt MT**, if requested by architect.
- C. Maintenance literature: Submit one (1) copy of manufactures maintenance instructions.

1.04 DELIVERY, STORAGE AND HANDLING

- A. Flooring contractor shall not deliver material to the job site until the work of the other trades has been completed where the flooring is to be installed.
- B. All Action QuickCourt MT materials should be acclimated to the jobsite conditions for a minimum of 24 hours prior to beginning the installation. Store and secure all materials on a flat and dry surface.

1.05 WORKING CONDITIONS

- A. The flooring shall not be installed until all trades and painters have finished in floor area.
- B. The concrete slab shall be dry, free of foreign materials, and turned over to the flooring contractor broom clean.
- C. The installation area shall be closed to all traffic and activity for a period to be set by the flooring contractor.

1.06 WARRANTY

- A. Action Floor Systems, LLC. warrants the material supplied to be free from manufacturing defects for a period of sixteen (16) years as set forth in the manufacturer's standard warranty. The exclusive remedy under this warranty shall be replacement of defective material supplied by Action Floor Systems, LLC. or correction of defective installation by the flooring installer for a period of one (1) year. All implied warranties of merchantability or fitness for intended use are limited to the period of this warranty. This warranty excludes consequential damages.
- B. This warranty does not cover damage caused by fire, winds, floods, chemicals, or other abuse, or by failure of other contractors to adhere to specifications. This warranty also excludes damage to floors due to ordinary wear and tear, misuse, abuse, neglect, faulty construction of the building, (other than the flooring installation), separation of the concrete slab underlying the floor, settlement of the walls, or unprofessional installation.
- C. Installer (Flooring Contractor) shall warrant installation for a period of one (1) year after the floor has been substantially installed and completed.

PART 2 - PRODUCTS

2.01 MATERIALS

- A. Flooring shall be Non-Slip Multipurpose Action QuickCourt MT suspended modular flooring.
 - 1. Open top design shall be 250mm x 250mm x 19.1mm (9.84" x 9.84" x 3/4"), high impact polypropylene suspended floor tile with 841 individual support legs. Weight 226.79g (8 oz).
- B. Standard tile colors as stated on color card.
- C. Game line paint as approved by Action Floors Systems, LLC. Colors are to be selected from the approved chart. Adhere to all MSDS requirements for materials supplied.
 - 1. Primer shall be of proprietary formulation as supplied by Action Floor Systems, LLC.
 - 2. Paint shall be a two-component polyurethane as recommended by Action Floor Systems, LLC..
- D. Product Test results:

1. Flame Spread Index	ASTM E84	90
2. Smoke Generation	ASTM E84	90
3. Friction	ASTM C1028	Dry 0.65, Wet 0.64
4. Compression vs. Crush	ASTM D3998	No Break
5. Noise Reduction Coefficient	ASTM C423	5-10%
6. Rolling Load	DIN 18032-2	Pass
7. Standard Deformation	DIN 18032-2	0.9mm
8. Ball Rebound	DIN 18032-2	98%
9. Load Bearing Capacity	DIN 18032-2	180 psi
10. R-Value		X<1.0
11. Flatness		0.0mm
12. Lateral Movement		0.00"- 0.035"

