




ACTION SL DECO

SYSTEM TYPE: Commercial – Industrial Floor System



Action SL Ultra system: 2.25mm total thickness

Performance Meets or Exceeds:

Density Resin + Hardener	~1500 kg/m3
Surface Hardness (DIN 53505)	D 65
Elongation at Break (DIN 54555)	95%
Tensile Strength (DIN 53455)	4 MP a

Multi-use indoor Commercial – Institutional – Retail

Applications: Schools, Libraries, Hotels, Offices, Retail Shops, Rehabilitation & Care Facilities

LEED:



- Supplied by a zero-waste company
- Meets all criteria and certified under Eco Specifier Product Assessment Certificate
- Supplied by ISO 14000:2006-certified company

System Qualities:

- Hygienic and simple to clean
- Seamless surface
- Solvent-free, self-leveling floor system
- Environmentally responsible
- Industry's strongest structural layer

* Sustainable Construction Of Renewable Engineered Surfaces. Action has been certified as a Carbon Negative provider following a Life Cycle Assessment conducted by the University of Wisconsin and Carbon Clear, an international independent auditor of manufacturing carbon profiles.

- Environmentally-smart system engineered to focus materials where needed for durability and performance.
- Manufacturer and flooring system independently verified by guidelines of the ISO 9000 and 14001.
- Accredited “Ecospecifier” product for achievement of Green Building Rating Tool Credits.
- Flooring system shall be supplied by a Carbon Negative company on the basis of an earned carbon negative status.



ACTION FLOOR SYSTEMS, LLC
4781 N. US Hwy 51 • Mercer, WI 54547

TOLL FREE: 800-746-3512 • VOICE: 715-476-3512
FAX: 715-476-3585 • EMAIL: info@actionfloors.com

actionfloors.com