




Atelier Dance Floor System

SYSTEM TYPE: FLOATING RESILIENT



Stable, balanced double layer 15/32" (12 mm) thick, APA exposure 1 rated sheathing minimum APA span rating of 32/16.

Factory-exact, computer-cut, performance flex kerfs.

Monolithic foam dampening for the ultimate dance activity resilience.

**MFMA NORTHERN HARD MAPLE
BY ACTION:**

Random Length (RL).
Action Long Length (FJ)
Expansion Ridge Technology (ERT)

TESTING AGENCY:

Certified by ISSS

PERFORMANCE MEETS OR EXCEEDS:

EN 14904, ANSI E1.26-2006 (R2012)

SLAB DEPRESSION:

25/32" (20 mm): 2-1/4" (56 mm)

LEED:



FloorScore®-certified
Proprietary certified EPD®
FSC®-certified Maple and Subfloor available
MR credits – based on products, selected materials and facility locations


PERFORMANCE AND SYSTEM STABILITY:

- Stable double layer APA rated sheathing subfloor system
- Other performance foam options available
- SCORES Compliant
- Performance can be matched to activity needs through pad options
- Excellent floor uniformity



ISO 14001:2004 VERIFIED

- Features the proven stability and flexibility of double layer 15/32" (12 mm) sheathing subfloor design.
- The manufacturer and flooring shall be independently verified by the guidelines of the ISO 14040:2006 and ISO 14044:2006 Life Cycle Assessment (LSA) confirming a negative carbon footprint.
- Carbon Evaluation must be inclusive and based on all corporate facilities, offices and mills.
- The manufacturer and flooring shall be independently verified by the guidelines of the ISO 14064-1:2006 World Resources Institute Greenhouse Gas Protocol, Scope 1, 2 and 3.
- The manufacturer and flooring shall be registered in the Collaborative for High Performance Schools (CHPS) Product Database.
- Floor system manufacturer must provide a Life Cycle Assessment and an Environmental Product Declaration (EPD®) in accordance with the Product Category Rule Version 2.2014.
- Floor system manufacturer must be FloorScore® Certified in accordance with CDPH 01350.



Action_Atelier

201912

Complete product specifications and system drawings are available online at: www.actionfloors.com



ACTION FLOOR SYSTEMS, LLC
 4781 N. US Hwy 51 • Mercer, WI 54547
 TOLL FREE: 800-746-3512 • VOICE: 715-476-3512
 FAX: 715-476-3585 • EMAIL: info@actionfloors.com
actionfloors.com

Rev 11/20