


AmpOne™ Floor System

SYSTEM TYPE: FLOATING RESILIENT



MFMA NORTHERN HARD MAPLE **BY ACTION:**

Random Length (RL) Action Long Length (FJ) Expansion Ridge Technology (ERT)

Certified by ISSS **TESTING AGENCY:**

PERFORMANCE MEETS OR EXCEEDS:

25/32" (20 mm): 2-1/8" (54 mm) **SLAB DEPRESSION:**

LEED:











FloorScore®-certified Proprietary certified EPD® FSC®-certified Maple and Subfloor available MR credits – based on products, selected materials and facility locations

PERFORMANCE & SYSTEM STABILITY:

- Unitized factory fabricated subfloor system
- 7/16" (11 mm) Continuous pad design delivers:
 - Exceptional uniformity
 - Great ball bounce
- SCORES Compliant
- System features a low profile height
- Efficient double layer system
- Uniform & consistent playing surface






















- Delivers uniform surface, the floor system can be tuned to meet your performance expectations.
- The manufacturer and flooring shall be independently verified by the guidelines of the ISO 14040:2006 and ISO 14044:2006 Life Cycle Assessment (LSA) confirming a negative carbon footprint.
- Carbon Evaluation must be inclusive and based on all corporate facilities, offices and mills.
- The manufacturer and flooring shall be independently verified by the guidelines of the ISO 14064-1:2006 World Resources Institute Greenhouse Gas Protocol, Scope 1, 2 and 3.
- The manufacturer and flooring shall be registered in the Collaborative for High Performance Schools (CHPS) Product Database.
- Floor system manufacturer must provide a Life Cycle Assessment and an Environmental Product Declaration (EPD®) in accordance with the Product Category Rule Version 2.2014.
- Floor system manufacturer must be FloorScore® Certified in accordance with CDPH 01350.



Complete product specifications and system drawings are available online at: www.actionfloors.com



ACTION FLOOR SYSTEMS, LLC 4781 N. US Hwy 51 • Mercer, WI 54547

TOLL FREE: 800-746-3512 • VOICE: 715-476-3512 FAX: 715-476-3585 • EMAIL: info@actionfloors.com